



## EL 2.5CAHT5




Pitch:5.00 mm



## EL 2.5CAVT5



Pitch:5.00 mm



IEC 数据	刚性导线 (mm <sup>2</sup> )	柔性导线 (mm <sup>2</sup> )	AWG	I (A)	U (V)
连接数据	0.2-2.5	0.2-2.5	24-14	24	250
绝缘材料组别	I				
污染等级	3 2 2				
过电压类别	III III II				
额定电压(V)	250 320 630				
额定冲击电压(KV)	4				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-/Nm)	M2.5/ 0.4-0.5				
剥线长度(mm)	9				
线路板孔径(mm)	Ø1.2				
引脚尺寸(mm)	0.8x0.8				

UL 数据					
额定电压(V)/电流(A)				300/15	
压线范围(AWG)				30-12	

IEC	Rigid (mm <sup>2</sup> )	flexible (mm <sup>2</sup> )	AWG	I (A)	U (V)
Connection data	0.2-2.5	0.2-2.5	24-14	24	250
Insulating Material Group	I				
Pollution degree	3 2 2				
Overvoltage Category	III III II				
Rate Voltage(V)	250 320 630				
Rate impulse Voltage(KV)	4				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-/Nm)	M2.5/ 0.4-0.5				
Stripping length(mm)	9				
PCB Hole Diameter(mm)	Ø1.2				
Pin Dimensions(mm)	0.8x0.8				

UL Technical Data					
Rate Voltage(V)/Current(A)				300/15	
Wire Range(AWG)				30-12	

位数/No. of positions	订货型号/Order No.
2	EL 2.5CAHT5-2-5.00
...	...
24	EL 2.5CAHT5-24-5.00

IEC 数据	刚性导线 (mm <sup>2</sup> )	柔性导线 (mm <sup>2</sup> )	AWG	I (A)	U (V)
连接数据	0.2-2.5	0.2-2.5	24-14	24	250
绝缘材料组别	I				
污染等级	3 2 2				
过电压类别	III III II				
额定电压(V)	250 320 630				
额定冲击电压(KV)	4				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-/Nm)	M2.5/ 0.4-0.5				
剥线长度(mm)	9				
线路板孔径(mm)	Ø1.2				
引脚尺寸(mm)	0.8x0.8				

UL 数据					
额定电压(V)/电流(A)				300/15	
压线范围(AWG)				30-12	

IEC	Rigid (mm <sup>2</sup> )	flexible (mm <sup>2</sup> )	AWG	I (A)	U (V)
Connection data	0.2-2.5	0.2-2.5	24-14	24	250
Insulating Material Group	I				
Pollution degree	3 2 2				
Overvoltage Category	III III II				
Rate Voltage(V)	250 320 630				
Rate impulse Voltage(KV)	4				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-/Nm)	M2.5/ 0.4-0.5				
Stripping length(mm)	9				
PCB Hole Diameter(mm)	Ø1.2				
Pin Dimensions(mm)	0.8x0.8				

UL Technical Data					
Rate Voltage(V)/Current(A)				300/15	
Wire Range(AWG)				30-12	

位数/No. of positions	订货型号/Order No.
2	EL 2.5CAVT5-2-5.00
...	...
24	EL 2.5CAVT5-24-5.00