

Ordering Information

RF3XX-X XX X X X S XXX 1

HEIGHT OF HOUSING	1:Single-Row	NO. OF PINS PER ROW	0:No Pitch	A=1u"	A:PBT	LENGTH OF TERMINAL
39:3.9mm	2: Dual-Row	1~40P	1:1.27	B=2u"	B:PA6T	
40:4.0mm	3: Three Rows of	2~40P	2:2.00	C=5u"	C:PA9T	
41:4.1mm		3~40P	3:2.54	D=10u"	D:LCP	
			4:7.62	E=15u"	G:PPS	
			5:10.16	F=30u"		
			6:15.24	S=Ordinary Tin Plated		
			7:22.86	H=Half gold plated Tin		

Stright socket connector:solder tail
single row
Availability from:2 to 50 contacts
Standard number of contacts 25 and 50









Stright socket connector:solder tail
double row
Availability from:4 to 100 contacts
Standard number of contacts 50 and 100

Stright socket connector:solder tail
double row with 2.54mm rowto row distance
Availability from:4 to 100 contacts
Standard number of contacts 100

Stright socket connector:solder tail
triple row
Availability from:6 to 150 contacts
Standard number of contacts 150

Specifications

Insulator : Black glass filled polyester PPS-GF30-FR
Flammability : UL94V-0
Sleeve : Brass CuZn 36Pb3(36000)
Contact clip(3 finger) : Beryllium copper (C17200)
Mating pin ϕ : 0.38 to 0.50 mm
Forces : (polished steel gauge ϕ 0.41mm)
-Insertion : 0.5 N typ
-Withdrawal : 0.2 N typ
Mechanical life : min 500 cycles
Rated current : 1Amp
Contact resistance: Max 10m Ω
Dielectric resistance : Min 500V_{RMS}



上海高霖电子有限公司

卢小强

PART NO.

RF3XX-XXXXXXSXXX1

TITLE:

1.27圆孔排母 180度

Customer No.

					OPERATION		SCALE		Fit	
					X.X	±0.25	UNIT		MM	
					X.XX	±0.20	SIZE	A4	DESIGN	
					X.XXX	±0.10	SHEET	1/1	CHECK	
					Angle	±3°	PROJ.	☉	APPROVE	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL				

1 2 3 4 5 6 7 8 9 10