



EL 3AT



Pitch: 5.08 (5.00) mm



35 angled connection

IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.2-4	0.2-2.5	24-12	28	250
绝缘材料组别	I				
污染等级	3				
过电压类别	III				
额定电压(V)	250 320 630				
额定冲击电压(KV)	4				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-Nm)	M3/0.5-0.6				
剥线长度(mm)	8				
线路板孔径(mm)	Ø 1.3				
引脚尺寸 (mm)	0.7x1.0				

UL 数据

额定电压(V)/电流(A)	300/15
压线范围(AWG)	30-12

IEC Technical Data	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.2-4	0.2-2.5	24-12	28	250
Insulating Material Group	I				
Pollution degree	3				
Overvoltage Category	III				
Rate Voltage(V)	250 320 630				
Rate impulse Voltage(KV)	4				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-Nm)	M3/0.5-0.6				
Stripping length(mm)	8				
PCB Hole Diameter(mm)	Ø 1.3				
Pin Dimensions(mm)	0.7x1.0				

UL Technical Data


Rate Voltage(V)/Current(A)	300/15
Wire Range(AWG)	30-12

位数/No. of positions	订货型号/Order No.
2	EL 3AT-2-5.00
3	EL 3AT-3-5.00
2	EL 3AT-2-5.08
3	EL 3AT-3-5.08

EL 5HT



Pitch: 6.35 mm



IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.2-6	0.2-4	24-10	32	500
绝缘材料组别	I				
污染等级	3				
过电压类别	III				
额定电压(V)	500 630 1000				
额定冲击电压(KV)	6				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-Nm)	M3/0.5-0.6				
剥线长度(mm)	8				
线路板孔径(mm)	Ø 1.3				
引脚尺寸 (mm)	0.9x0.9				

UL 数据

额定电压(V)/电流(A)	300/30
压线范围(AWG)	30-10

IEC Technical Data	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.2-6	0.2-4	24-10	32	500
Insulating Material Group	I				
Pollution degree	3				
Overvoltage Category	III				
Rate Voltage(V)	500 630 1000				
Rate impulse Voltage(KV)	6				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-Nm)	M3/0.5-0.6				
Stripping length(mm)	8				
PCB Hole Diameter(mm)	Ø 1.3				
Pin Dimensions(mm)	0.9x0.9				

UL Technical Data


Rate Voltage(V)/Current(A)	300/30
Wire Range(AWG)	30-10

位数/No. of positions	订货型号/Order No.
2	EL 5HT-2-6.35
3	EL 5HT-3-6.35

EL 5HT



Pitch: 7.62 mm



IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.2-6	0.2-4	24-10	32	500
绝缘材料组别	I				
污染等级	3				
过电压类别	III				
额定电压(V)	500 630 1000				
额定冲击电压(KV)	6				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-Nm)	M3/0.5-0.6				
剥线长度(mm)	8				
线路板孔径(mm)	Ø 1.3				
引脚尺寸 (mm)	0.9x0.9				

UL 数据

额定电压(V)/电流(A)	300/30
压线范围(AWG)	30-10

IEC Technical Data	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.2-6	0.2-4	24-10	32	500
Insulating Material Group	I				
Pollution degree	3				
Overvoltage Category	III				
Rate Voltage(V)	500 630 1000				
Rate impulse Voltage(KV)	6				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-Nm)	M3/0.5-0.6				
Stripping length(mm)	8				
PCB Hole Diameter(mm)	Ø 1.3				
Pin Dimensions(mm)	0.9x0.9				

UL Technical Data

Rate Voltage(V)/Current(A)	300/30
Wire Range(AWG)	30-10

位数/No. of positions	订货型号/Order No.
2	EL 5HT-2-7.62
3	EL 5HT-3-7.62