



ES 1.5ATD



Pitch:3.5 mm



45 a ngled connection

IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.5-1.5	0.5-1.5	20-16	2	250
绝缘材料组别	I				
污染等级	3				
过电压类别	III				
额定电压(V)	250				
额定冲击电压(KV)	4				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-Nm)	\				
剥线长度(mm)	8				
线路板孔径(mm)	Ø1.0				
引脚尺寸 (mm)	0.4X0.8				

UL 数据

额定电压(V)/电流(A)	300/2
压线范围(AWG)	24-16


IEC Technical Data	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.5-1.5	0.5-1.5	20-16	2	250
Insulating Material Group	I				
Pollution degree	3				
Overvoltage Category	III				
Rate Voltage(V)	250				
Rate impulse Voltage(KV)	4				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-Nm)	\				
Stripping length(mm)	8				
PCB Hole Diameter(mm)	Ø1.0				
Pin Dimensions(mm)	0.4X0.8				

UL Technical Data


Rate Voltage(V)/Current(A)	300/2
Wire Range(AWG)	24-16

位数/No. of positions	订货型号/Order No.
2	ES 1.5ATD-2-3.5
...	...
24	ES 1.5ATD-24-3.5

ES 1.5AT



Pitch:3.5 mm



45 a ngled connection

IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.5-1.5	0.5-1.5	20-16	2	250
绝缘材料组别	I				
污染等级	3				
过电压类别	III				
额定电压(V)	250				
额定冲击电压(KV)	4				
绝缘材料/阻燃等级 UL 94	PA/V0				
螺钉/扭矩(-Nm)	\				
剥线长度(mm)	8				
线路板孔径(mm)	Ø1.0				
引脚尺寸 (mm)	0.4X0.8				

UL 数据

额定电压(V)/电流(A)	300/2
压线范围(AWG)	24-16

IEC Technical Data	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.5-1.5	0.5-1.5	20-16	2	250
Insulating Material Group	I				
Pollution degree	3				
Overvoltage Category	III				
Rate Voltage(V)	250				
Rate impulse Voltage(KV)	4				
Insulating material/Inflammability Class	PA/V0				
Screw/Torque(-Nm)	\				
Stripping length(mm)	8				
PCB Hole Diameter(mm)	Ø1.0				
Pin Dimensions(mm)	0.4X0.8				

UL Technical Data

Rate Voltage(V)/Current(A)	300/2
Wire Range(AWG)	24-16

位数/No. of positions	订货型号/Order No.
2	ES 1.5AT-2-3.5
...	...
24	ES 1.5AT-24-3.5